





SE30WS1-02







S ወ Ĵ S Ď





SE30WS2-05





SE30WS3-04

Specification

Product Name Pile Construction Tufted Yarn Weight Face Yarn Type Dye Method Machine Gauge Primary Backing Secondary Backing Pile Thickness Total Thickness Tile Size

Performance Test

Flammability

Smoke Density

Static Generation

Colourfastness to Water

Colourfastness to Light

Colourfastness to Crocking Tensile Strength Test

Sense Texture Multi-Level Loop 520g/m² 100% Bulk Continuous Filament Fiber 100% Solution Dyed 1/12 Polyester Premium Fabric PVC with Fibreglass 3.5mm ± 0.5 5.5mm ± 0.5

Pass GB 8624-2006 Pass GB/T 14768-93 Pass ASTM E-662 <=450 DMC Pass GB 8624-2006 Pass AATCC-134 Pass GB/T 18044-2000 Pass AATCC-16E Pass Grade 4/5 ISO 105-X12 Pass BS EN ISO 105 E01:1996 Pass AATCC-16E Pass Grade 5 ISO B02:1994E Pass BS EN ISO 105 B02:1999 Pass BS EN ISO 105-X12:2002 Pass ISO 13934-1 Warp 3112.9

50cm x 50cm



Disclaimer

- This carpet is manufactured and sold for floorcovering use only.
- As with all carpets, colours are subject to dye lot variations.
- All carpet specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice.
- "Tufted Pile Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting, shearing and carving will result in a lower finished yarn weight in purchased carpets.



SE30WS1-02



SE30WS3-04



SE30WS4-03



SE30WS2-05







MODULAR malaysia