







Random

MMODULAR

## Specification

Product Name
Pile Construction
Tufted Yarn Weight
Face Yarn Type
Dye Method
Machine Gauge
Primary Backing
Secondary Backing
Pile Thickness
Total Thickness

## **Performance Test**

Flammability

Tile Size

Smoke Density

Static Generation

Colourfastness to Water

Colourfastness to Light

Colourfastness to Crocking Tensile Strength Test Random Level Loop 400g/m²

100% Bulk Continuous Filament Fiber

100% Solution Dyed

1/12

Polyester Premium Fabric PVC with Fibreglass 3.5mm ± 0.5

5.5mm ± 0.5 50cm x 50cm

Pass GB 8624-2006 Pass GB/T 14768-93

Pass ASTM E-662 <=450 DMC

Pass GB 8624-2006 Pass AATCC-134 Pass GB/T 18044-2000 Pass AATCC-16E

Pass Grade 4/5 ISO 105-X12 Pass BS EN ISO 105 E01:1996

Pass AATCC-16E

Pass Grade 5 ISO B02:1994E Pass BS EN ISO 105 B02:1999 Pass BS EN ISO 105-X12:2002 Pass ISO 13934-1

Warp 3112.9

## Disclaimer

- This carpet is manufactured and sold for floorcovering use only.
- As with all carpets, colours are subject to dye lot variations.
- All carpet specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice.
- "Tufted Pile Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting, shearing and carving will result in a lower finished yarn weight in purchased carpets.



RA01LV01-01



RA01LV03-03



RA01LV02-02



RA01LV04-04

